

Ni-MH Battery

Nickel Metal Hydride Battery

NH-A2100 Brief Datasheet



1. BASIC SPECIFICATION:

Model		NH-A2100	Nominal Voltage		1.2V
Charge	Standard	210mA for 16hrs	Capacity	Typical	2150mAh (0.2C discharge)
	Fast	2100mA for about 75min		Minimum	2100mAh (0.2C discharge)
Life Cycles		500cycles	Internal Impedance		Less than 15m
Weight		Approx. 36g	Discharge Temp.		-10°C to 50°C
Charge Temp.	Standard	0°C to 40°C	Storage Temp.	< 1 year	-10°C to 30°C
	Fast	10°C to 40°C		< 3 month	-10°C to 40°C
Discharge Cut-off Voltage		1.0V			


2. MAIN FEATURES

- Ni-MH battery features the same voltage (1.2V) as Ni-CD, yet twice the capacity.
- Wide operational temperature range from -10°C to 50°C.
- Self-discharge is minimized to levels below Ni-CD for enhanced storage characteristics.
- Quick charging in about one hour is possible with a specially designed Ni-MH exclusive charger..


3. ELECTRICAL CHARACTERISTICS



Note: Any representations in this brochure concerning performance, are for informational purposes only and are not construed as warranties either expressed or implied, of future performance.



4, BATTERY DIMENSION



4. WARNING!

- * Do not short-circuit, disassemble, deform, heat or place the battery near a direct flame. Any of the above actions could cause it to ignite explode or become damaged.
- * Do not weld directly batteries.
- * Do not reverse polarity when charging the battery.
- * Do not connect the anode and cathode with metals like wires.
- * Please store batteries in a cool dry place.
- * Keep the battery out of the reach of children.

Note: Any representations in this brochure concerning performance, are for informational purposes only and are not construed as warranties either expressed or implied, of future performance.